



# **AccuMax™**

# Single-Use Holmium Laser Fiber

Laser compatibility is a key criteria for laser fiber performance. The AccuMax Fibers are recommended for use on Dornier and New Star Laser Systems.

### **Polished Output Tip**

Designed to remove sharp edges and reduce imperfections that can occur from mechanical or hand cleaving.

Damaged output tips can result in redirection or reflection of laser energy away from the fiber tip and potential for decreased output efficiency.<sup>1</sup>


### **Improved Durability**

Custom construction and materials are designed to reduce thermal breakdown and scope damage in flexible ureteroscopes.

The AccuMax 200 Fiber can withstand a 1.0cm bend diameter when used on a Dornier Medilas H Laser at 1.5J and 10 Hz.<sup>2</sup>



Both fibers shown at approximately 15x actual diameter. Both fibers are brand new, out of the package.



### **High Output Efficiency**

The AccuMax™ Guided Connector is designed to direct laser energy towards the core for high output efficiency and to diffuse errant energy within the connector that may cause overfill.

### **Irrigation and Visibility**

Smaller OD fiber designed to increase irrigation and visibility.

# Custom Guided Connector

with polished end designed to deliver high output efficiency and consistent performance

### **Full Deflection**

AccuMax 200 Fiber deflects 270 degrees in a flexible ureteroscope, facilitating the ability to reach all areas of the renal pelvis during flexible ureteroscopy.<sup>2</sup>

Fiber flexibility is an important variable in terms of accessing renal stones and improving ureteroscope deflection longevity.<sup>3</sup>




# Dornier Brand DUR270D Fiber 455 microns AccuMax 200 Fiber 415 microns AccuMax 200 Fiber 415 microns

AccuMax 200 Fibers were shown to be 30% more flexible than Dornier DUR270D Fibers² (grams force)

AccuMax 200 Fiber 5.0

Dornier Brand DUR270D Fiber 7.1

## **AccuMax**™ Single-Use Holmium Laser Fiber Ordering Information



Product code	Description	Maximum input wattage	Units
M006 <b>840401</b> 0	AccuMax 200	20 watts	Each
M006 <b>840401</b> 2	AccuMax 200	20 watts	Box/5
M006 <b>84 0402</b> 0	AccuMax 365	100 watts	Each
M006 <b>840402</b> 2	AccuMax 365	100 watts	Box/5
M006 <b>840403</b> 0	AccuMax 550	100 watts	Each
M006 <b>840403</b> 2	AccuMax 550	100 watts	Box/5
M006 <b>840404</b> 0	AccuMax 1000	100 watts	Each
M006 <b>840404</b> 2	AccuMax 1000	100 watts	Box/5

Please consult your sales representative for more information and ordering details. To learn more visit **www.bostonscientific.com/Urology** 



<sup>2.</sup> Bench Testing on file with Boston Scientific. Bench testing not necessarily indicative of clinical performance

CAUTION: U.S. Federal law restricts this device to sale by or on the order of a physician.

CAUTION: The law restricts these devices to sale by or on the order of a physician. Indications, contraindications, warnings and instructions for use can be found in the product labeling supplied with each device. Information for use only in countries with applicable health authority registrations. Material not intended for use in France.

Refer to package insert provided with these products for complete Instructions for Use, Contraindications, Warnings, Precautions, Adverse Events, and Instructions prior to using this product.

All trademarks are the property of their respective owners.



Boston Scientific Corporation 300 Boston Scientific Way Marlborough, MA 01752 www.bostonscientific.com

Ordering Information 1.888.272.1001

© 2017 Boston Scientific Corporation or its affiliates. All rights reserved.

URO-482314-AA NOV 2017

<sup>3.</sup> Mues AC, Teichman JM, Knudsen BE. Evaluation of 24 holmium:YAG laser optical fibers for flexible ureteroscopy. *J Urol.* 2009 Jul;182(1):348-54.