

LATITUDE Link™
HL7 SPECIFICATION

LATITUDE Link™ System

Outdated version. Do not use.
Version überholt. Nicht verwenden.
Version obsolète. Ne pas utiliser.
Versión obsoleta. No utilizar.
Versione obsoleta. Non utilizzare.
Verouderde versie. Niet gebruiken.
Föråldrad version. Använd ej.
Παλιά έκδοση. Μην χρησιμοποιείτε.
Versão obsoleta. Não utilize.
Forældet version. Må ikke anvendes.
Zastaralá verzia. Nepoužívať.
Utdatert versjon. Skal ikke brukes.
Zastaraná verzia. Nepoužívať.
Elavult verzió. Ne használja!
Wersja nieaktualna. Nie używać.

Outdated version. Do not use.
Version überholt. Nicht verwenden.
Version obsolète. Ne pas utiliser.
Versión obsoleta. No utilizar.
Versione obsoleta. Non utilizzare.
Verouderde versie. Niet gebruiken.
Föråldrad version. Använd ej.
Παλιά έκδοση. Μην την χρησιμοποιείτε.
Versão obsoleta. Não utilize.
Forældet version. Må ikke anvendes.
Zastaralá verze. Nepoužívat.
Utdatert versjon. Skal ikke brukes.
Zastaraná verzia. Nepoužívať.
Elavult verzió. Ne használja!
Wersja nieaktualna. Nie używać.

LATITUDE Link™ HL7 Message Schematic

SEGMENT	DATA CONTAINED WITHIN SEGMENT	PAGE
MSH	MESSAGE HEADER	2
PID	PATIENT IDENTIFICATION	3
NTE 1	NOTES AND COMMENTS	4
NTE 2		
NTE 3		
NTE 4		
PV 1	PATIENT VISIT	5
OBR 1	LAST INTERROGATION OBSERVATION REPORT	9
OBX		
OBR 2	IMPLANT OBSERVATION REPORT	17
OBX		
OBR 4	LEAD INFORMATION OBSERVATION REPORT	18
OBX		
ZU 1	PATIENT DETAILS SCREEN URL	8
ZU 2	LATITUDE MESSAGE VERSION	8

TABLE OF CONTENTS

Overview	1
LATITUDE HL7 Message Specification	1
MSH segment structure	2
PID segment structure	3
NTE segment structure	4
PV1 segment structure	5
OBR segment structure	5
OBX segment structure	7
ZUx segment structure	8
LATITUDE Link HL7 Term Definitions	9
OBX terms used in OBR–1 group (Last interrogation data)	9
OBX terms used in OBR–2 group (Implant data)	17
OBX terms used in OBR–4 group (Lead information data)	18
Example HL7 File	20
Symbols Used on Labeling	22

Overview

The Boston Scientific LATITUDE Link™ application creates HL7 Observation Result Unsolicited (ORU) messages according to the specifications and definitions published in this document. These messages are used to deliver patient data to Electronic Medical Record (EMR) systems.

This document is intended for Boston Scientific (BSC) customers who use EMR systems to track and manage patient data.

NOTE: *It is assumed that readers of this section are familiar with HL7 2.x terminology, specification syntax, data types, message structures, and semantics for ORU messages. For more information concerning HL7 messaging, visit www.hl7.org.*

LATITUDE HL7 Message Specification

The LATITUDE HL7 file is based upon the HL7 2.3.1 Observation Result Unsolicited message standard. This international standard describes a universal model for medical electronic data interoperability.

LATITUDE HL7 message basic concepts: (ASCII characters shown as delimiters in this publication are examples and are subject to change.)

1. A LATITUDE message is made up of segments
2. The first three letters of a segment are the segment type identifier
3. A LATITUDE message will always contain these segment types: MSH; PID; NTE1; PV1; OBR1; OBX (many); ZU1; ZU2
4. *Segments* are ASCII text strings made up of several delimited *sequences*
5. A sequence is delimited by the pipe character (| , i.e., ASCII 0x7C) at its end
6. Sequences are located and referred to by their numeric position within the segment
7. The segment type identifier is not counted in sequence numbering
8. With the exception of segment type MSH, the first sequence is always a number. This and the three-character segment ID immediately before it are used to identify the segment, e.g. NTE.1, OBR.3, and OBX.75
9. Some sequences may contain sub-sequences:
 - Items within sub-sequences are separated by the caret character (^ , i.e., ASCII 0x5E)
 - The quantity and maximum length of sub-sequences are defined in the sequence definition
 - Empty sub-sequences use the caret character as a placeholder
 - The sub-sequence ends with a sequence delimiter (|)
10. Message segments end with either a LF or CR character.

Patient data within a message is organized into three observation reports: Last Interrogation, Implant, and Lead Information. Observation reports consist of a single OBR segment followed by multiple OBX segments.

The message also contains useful follow-up summary data, including additional information from LATITUDE's Quick Notes report.

Refer to the illustration at left for further information.

MSH segment structure

The MSH segment contains information about the sender and receiver of the message, the type of the message, a time stamp, etc. It is the first segment of the ORU message.

ELEMENT NAME	SEQ	SUB SEQ	DT	LEN	USAGE	CARD	TBL#	ITEM #	Fixed	Example Value
Field separator	1		ST	1	R	[1..1]		00001	Y	
Encoding characters	2		ST	4	R	[1..1]		00002	Y	^~\&
Sending application	3		HD	180	R	[1..1]		00003	Y	LATITUDE, LATITUDE LINK
Sending facility	4		HD	180	R	[1..1]		00004	Y	BOSTON SCIENTIFIC
Receiving facility	6		HD	180	RE	[0..1]		00006		Clinic Name
Date/Time of message	7		TS	26	R	[1..1]		00007		2006051015 0057+0000
Message type	9		MSG	15	R	[1..1]		00009		
Message code		1	ID	3	R	[1..1]	0076		Y	ORU
Trigger event		2	ID	3	R	[1..1]	0003		Y	R01
Message control ID	10		ST	20	R	[1..1]		00010		2500144
Processing ID	11		ID	1	R	[1..1]	0103	00011		P
Version ID	12		ID	5	R	[1..1]	0104	00012	Y	2.3.1
Accept acknowledgement type	15		ID	2	R	[1..1]	0155	00015	Y	NE
Character set	18		ID	6	R	[1..1]	0211	00692		8859/1 UNICODE See note 1
Principal language	19		CE	60	R	[0..1]		00693		See note 2
Language ID		1	ID	2	R	[0..1]				EN
Language name		2	ST	50	R	[0..1]				English
Coding system		3	ST	6	R	[0..1]				ISO639

MSH Notes

1. The Character Set identifier will be either 8859/1 or UNICODE, but not both. Boston Scientific reserves the right to change the character set used in the HL7 message. The system receiving this HL7 message should check MSH.18 in order to identify the character set used in this HL7 message.
2. When Principal Language is blank, assume EN^English^ISO639. Otherwise the message language will be identified.

PID segment structure

The PID segment contains patient identifier information such as name, id codes, zip code, and so on. This information is used for patient matching.

ELEMENT NAME	SEQ	SUB SEQ	DT	LEN	USAGE	CARD	TBL #	ITEM #	Fixed	Example Value
Set ID - PID	1		SI	1	R	[1..1]		00104	Y	1
Patient ID	2		CX	20	R	[1..1]		00105		
ID		1	ST	20	R	[1..1]				m:N119/ s:123456
Patient identifier list	3		CX	20	R	[1..1]		00106		
List of IDs		1	ST	20	R	[1..2]				m:N119/ s:123456
Patient name	5		XPN	140	R	[0..1]		00108		See note 1
Family+last name prefix		1	CM	40	RE	[0..1]				Doe
Given name		2	ST	40	RE	[0..1]				John
Date of birth	7		TS	26	RE	[0..1]		00110		19271209
Sex	8		IS	1	RE	[0..1]	0001	00111		M See note 2

PID notes

1. This table defines all patient ID elements used in the PID segment. Because every patient record is unique, messages might not contain each of the patient ID elements defined above.
2. The value U will appear if the patient's sex is unknown.

NTE segment structure

The NTE segment contains any device status information messages conveyed during an interrogation session. There may be as many as two NTE segments in a single LATITUDE HL7 message.

ELEMENT NAME	SEQ	SUB SEQ	DT	LEN	USAGE	CARD	TBL #	ITEM #	Fixed	Example Value
Set ID - NTE	1		SI	1	R	[1..1]		00096		1
Source of comment	2		ID	8	R	[1..1]		00097	Y	LATITUDE Link
Comment	3		FT	65536	R	[1..*]		00098		See content description in Note 1

NTE notes

- There is the potential for 2 NTE segments within each device follow-up message. The Set ID and description for these segments is as follows:
 - Set ID 1 - This NTE segment contains a report consisting of a list of device status information for a particular patient.
 - Set ID 2 - This NTE segment contains information about the device if it is in a noteworthy condition. It will contain a warning statement and information concerning the condition. If this NTE segment exists it should be treated as a high priority message to display to the end user.
- Not every LATITUDE HL7 message will contain both NTE segments.

PV1 segment structure

The PV1 (Patient Visit) segment contains information regarding the patient's attending physician.

ELEMENT NAME	SEQ	SUB SEQ	DT	LEN	USAGE	CARD	TBL #	ITEM #	Fixed	Example Value
Set ID - PV1	1		SI	4	R	[1..1]		00131	Y	1
Patient class	2		IS	1	R	[0..1]		00132	Y	R

OBR segment structure

OBR segments are the section headers for individual OBX interrogation information segments. They contain data such as timestamps, report identifier, and a unique system-generated identifier.

ELEMENT NAME	SEQ	SUB SEQ	DT	LEN	USAGE	CARD	TBL #	ITEM #	Fixed	Example Value
Set ID - OBR	1		SI	4	R	[1..1]		00237	Y	1 thru 4 See note 1
Filler order number	3		EI	22	R	[1..1]		00217		
Entity identifier		1	ST	15	R	[1..1]				Unique identifier See note 2
Universal Service ID	4		CE	200	R	[1..1]		00238		
Identifier		1	ST	50	R	[1..1]				BostonScientific-LastInterrogation See note 1
Text		2	ST	50	R	[1..1]				Last Interrogation See note 1
Observation date/time #	7		TS	26	R	[1..1]		00241		20140212
Observation end date/time #	8		TS	26	RE	[0..1]		00242		20140212
Ordering provider	16		XCN	120	RE	[0..1]		00226		
ID number		1	ST	50	RE	[0..1]				e.g. JHopkins, Cardiology, etc. See note 3
Placer field 1	18		ST	2	R	[1..1]		00253	Y	DR See note 4
Results rpt/status Chng - date/time +	22		TS	26	RE	[0..1]		00255		20140212
Result Status +	25		ID	1	R	[1..1]	0123	00258	Y	F

Observation Report Group IDs

Set ID	Name	Description	Universal Service ID identifier	Universal Service ID text
1	Last interrogation	This OBR contains observations from an in-clinic follow-up session.	BostonScientific-LastInterrogation	Last Interrogation
2	Implant	This OBR contains observations generated at the time the PG was implanted.	BostonScientific-Implant	Implant
4	Lead information	This OBR contains information about implanted leads.	BostonScientific-Leads	Lead Information

OBR Notes

1. The ORU message contains three OBR (Observation Report) segments, each having a different Set ID and Universal Service ID (see table above). Each OBR contains multiple OBX records with context-specific observations. Details concerning the specific OBX observations are listed in the OBX segment structure section on page 7 of this documentation.
2. LATITUDE Link generates one unique identifier and records it as **Filler Order Number** (OBR.3) in all three OBRs. The identifier does not change if observations are re-sent.
3. **Ordering Provider** (OBR.16) is the clinic name specified in the LATITUDE Link configuration. If no clinic name is specified, this sequence will contain the text "Unspecified".
4. **Placer Field 1** (OBR.18) is a value that is used to identify the type of observation being sent. It is always set to **DR** which stands for Diagnostic Report.

OBX segment structure

OBX segments contain data gathered during the most recent device interrogation.

ELEMENT NAME	SEQ	SUB SEQ	DT	LEN	USAGE	CARD	TBL #	ITEM #	Fixed	Example Value
Set ID - OBX	1		SI	4	R	[1..1]		00569		Sequential integer starting with 1
Value type	2		ID	2	R	[1..1]	0125	00570		ST or NM or DT or ED See note 1
Observation identifier	3		CE	590	R	[1..1]		00571		
Identifier		1	ST	80	R	[1..1]				See note 2
Text		2	ST	256	R	[1..1]				See note 2
Name of coding system		3	ST	20	R	[1..1]			Y	GDT-LATITUDE
Observation value	5		--	4000	RE	[0..1]				See note 3
Units	6		CE	60	RE	[0..1]				
Identifier		1	ST	20	RE	[0..1]				See note 4
Observation result status	11		ID	1	R	[1..1]	0085	00579	Y	F
Date/Time of the Observation	14		TS	26	C	[0..1]		00582		2006031717000 0+0000 See note 5

OBX Notes

- Value Type (OBX.2) is the format of the reported data: ST - String; NM - Number; DT - Date; ED - Encapsulated data.
- All observations are coded using LATITUDE specific terms. These terms are defined in the "LATITUDE Link HL7 Term Definitions" section beginning on page 9.
- Observation Value (OBX.5) is the actual reported data expressed in the format specified in OBX.2. The maximum length of this string is 4000, although a PDF-formatted report may make the string longer.
- OBX.6 contains the unit of measurement for data reported in OBX.5, if applicable. Units of measurement and decimal notation are localized.
- Date/Time of the Observation (OBX.14) is non-blank only if the timestamp of the given observation is different than the timestamp reported in OBR.7. This value is conditional because it is a required value in observation groups OBR-1 and it is not present in groups OBR-2 and OBR-4.

ZUx segment structure

The Z Segments are customized segments used to transfer LATITUDE specific information.

ELEMENT NAME	SEQ	SUB SEQ	DT	LEN	USAGE	CARD	TBL #	ITEM #	Fixed	Example Value
Segment Type	1		ST	3	R	[1..1]			Y	ZU1 or ZU2 See note 1
Value	2		ST	200	R	[1..1]				Report Type See note 1

ZUx Notes

1. The two Z segments used are:

- ZU1 - This value will be empty.
- ZU2 - Value contains LATITUDE Link message description and version, e.g. "Device Summary Report Version 5."

Outdated version. Do not use.
 Version überholt. Nicht verwenden.
 Version obsolete. Ne pas utiliser.
 Versión obsoleta. No utilizar.
 Versione obsoleta. Non utilizzare.
 Verouderde versie. Niet gebruiken.
 Föråldrad version. Använd ej.
 Παλιά έκδοση. Μην την χρησιμοποιείτε.
 Versão obsoleta. Não utilize.
 Forældet version. Må ikke anvendes.
 Zastaralá verze. Nepoužívat.
 Utdatert versjon. Skal ikke brukes.
 Zastaraná verzia. Nepoužívať.
 Elavult verzió. Ne használja!
 Wersja nieaktualna. Nie używać.

LATITUDE Link HL7 Term Definitions

The tables below are complete listings of OBX terms as used in the OBR groups. Not all terms are relevant to all devices; therefore, not all terms will be present in all messages.

OBX terms used in OBR–1 group (Last interrogation data)

Not every term appears in every message

GDT Code	Term Name	Description	Data Type	Unit
GDT-00001	Result Source	The Result Source identifies the source of the data (i.e. In-Clinic Interrogation)	ST	
GDT-00002	Device Manufacturer	Device manufacturer company name	ST	
GDT-00003	Device Type	The type of device	ST	
GDT-00004	Device Name	The name given to a device by the manufacturer	ST	
GDT-00005	Device Model Name	The device model name	ST	
GDT-00006	Device Model Number	The device model number	ST	
GDT-00007	Device Serial Number	The device serial number	ST	
GDT-00008	Battery Gauge	The percentage that represents the battery life.	NM	%
GDT-00009	Battery Status	Represents information about the current status of the battery.	ST	
GDT-00011	Charge Time	The charge time of the last capacitor reform.	NM	s
GDT-00012	Last Reform	The date of last capacitor reformation in the implanted device.	DT	
GDT-00013	VF Episodes	Total Ventricular Fibrillation Episodes: The number of episodes in the highest tachy zone detected since the Counters Since date.	ST	
GDT-00014	<ul style="list-style-type: none"> • VT Episodes • Tachy Episodes • VT Episodes (V>A) 	VT Episodes: VT Zone arrhythmias detected since the Counters Since date	ST	
GDT-00015	VT-1 Episodes	VT-1 Episodes: VT-1 Zone arrhythmias detected since the Counters Since date. The term name will be shown as either VT Episodes or Tachy Episodes, depending upon the implanted device.	ST	
GDT-00016	<ul style="list-style-type: none"> • Non-Sustained Ventricular Episodes • Non-Sustained Episodes 	Total Ventricular Tachycardia Non-Sustained Episodes: The number of Non-Sustained VT episodes detected since the Counters Since date	ST	
GDT-00017	<ul style="list-style-type: none"> • ATR Mode Switches • ATR Episodes 	ATR Mode Switches: The number of mode switches detected since the "Counters Since" date.	NM	

OBX terms used in OBR-1 group (Last interrogation data)

Not every term appears in every message

GDT Code	Term Name	Description	Data Type	Unit
GDT-00018	Afib Episodes	Atrial Fibrillation Episodes: Atrial Fibrillation episodes detected since the "Counters Since" date.	NM	
GDT-00019	<ul style="list-style-type: none"> • SVT Episodes • SVT Episodes (V≤A) 	Supraventricular (Atrial) Tachycardia Episodes: SVT (AT) episodes detected since the "Counters Since" date.	NM	
GDT-00020	Atrial Percent Paced	Right Atrial Pacing Percent: The percent of all Right atrial events detected since the Counters Since date that were paced.	NM	%
GDT-00021	RV Percent Paced	Right Ventricular Pacing Percent: The percent of all Right ventricular events detected since the Counters Since date that were paced.	NM	%
GDT-00022	LV Percent Paced	Left Ventricular Pacing Percent: The percent of all left ventricular events detected since the Counters Since date that were paced.	NM	%
GDT-00023	Right Atrial Lead Status	The current status of the Right Atrial Lead determined by the device based on analysis of the lead amplitude and impedance.	ST	
GDT-00024	RA Intrinsic Amplitude	Right Atrial Intrinsic Amplitude (P-Wave) measured during an Intrinsic Amplitude Test.	ST	mV
GDT-00025	RA Pace Impedance	Right Atrial Lead Impedance measured during a Lead Impedance Test.	ST	Ohms
GDT-00026	Right Ventricular Lead Status	The current status of the Right Ventricular Lead determined by the device based on analysis of the lead amplitude and impedance.	ST	
GDT-00027	RV Intrinsic Amplitude	Right Ventricular Intrinsic Amplitude (R-Wave) measured during an Intrinsic Amplitude Test.	ST	mV
GDT-00028	RV Pace Impedance	Right Ventricular Lead Impedance measured during a Lead Impedance Test.	ST	Ohms
GDT-00029	<ul style="list-style-type: none"> • LV Lead Status • Left Ventricular Lead Status 	The current status of the Left Ventricular Lead determined by the device based on analysis of the lead amplitude and impedance.	ST	
GDT-00030	LV Intrinsic Amplitude	Left Ventricular Intrinsic Amplitude (R-Wave) measured during an Intrinsic Amplitude Test.	ST	mV
GDT-00031	LV Pace Impedance	Left Ventricular Lead Impedance measured during a Lead Impedance Test.	ST	Ohms

OBX terms used in OBR-1 group (Last interrogation data)

Not every term appears in every message

GDT Code	Term Name	Description	Data Type	Unit
GDT-00032	Shock Vector Status	The current status of the Shock Vector determined by the device based on analysis of the impedance.	ST	
GDT-00033	Shock Impedance	The daily measured value for shock impedance.	ST	Ohms
GDT-00034	V-Tachy Mode	Ventricular Tachy therapy mode.	ST	
GDT-00036	Brady Mode	Brady Mode (i.e., pacing mode): The manner in which a device provides rate and rhythm support.	ST	
GDT-00037	Lower Rate Limit	Lower Rate Limit (LRL) is the rate at which the implanted device paces the atrium and/or ventricle in the absence of sensed intrinsic activity.	NM	min ⁻¹
GDT-00038	Maximum Tracking Rate	Maximum Tracking Rate: In the DDDI and I(R) modes, the Maximum Tracking Rate (MTR) is the maximum rate at which the ventricular pacing will track 1:1 with nonrefractory sensed atrial events.	NM	min ⁻¹
GDT-00039	Maximum Sensor Rate	The fastest sensor-driven pacing rate that can be achieved in a rate-adaptive pacing system.	NM	min ⁻¹
GDT-00040	Sensitivity RA	Right Atrial Sensitivity: The Atrial Sensitivity parameter indicates the smallest signal that will be sensed in the right atrium. Value can be numeric value expressed in mV, a text string of (Nominal, Less, Least), or a combination of both.	ST	mV
GDT-00041	Sensitivity RV	Right Ventricular Sensitivity: The Right Ventricular Sensitivity parameter indicates the smallest signal that will be sensed in the right ventricle. Value can be numeric value expressed in mV, a text string of (Nominal, Less, Least), or a combination of both.	ST	mV
GDT-00042	Sensitivity LV	Left Ventricular Sensitivity: The Left Ventricular Sensitivity parameter indicates the smallest signal that will be sensed in the left ventricle. Value can be numeric value expressed in mV, a text string of (Nominal, Less, Least), or a combination of both.	ST	mV
GDT-00043	Paced AV Delay	The value of the AV Delay setting.	ST	ms

OBX terms used in OBR-1 group (Last interrogation data)

Not every term appears in every message

GDT Code	Term Name	Description	Data Type	Unit
GDT-00044	Sensed AV Offset	Sensed AV Offset: The AV Delay is shortened by the programmed Sensed AV Offset after a sensed atrial event. For COGNIS, TELIGEN, and newer devices a value may be displayed even if it is not applicable for the current programmed mode.	ST	ms
GDT-00045	AV Search Hysteresis Search Interval	Number of paced AV cycles between A-V rate searches.	ST	cycles
GDT-00046	AV Search Hysteresis AV Increase	The percentage increase in AV delay to be applied to the next cardiac cycle when AV Search is active.	NM	%
GDT-00047	<ul style="list-style-type: none"> • A-Refractory (PVARP) • A-Refractory 	Post-Ventricular Atrial Refractory Period (PVARP) is the time period after a ventricular event, either paced or sensed, when activity in the atrium does not reset the cardiac cycle nor trigger a ventricular stimulus.	ST	ms
GDT-00048	RV-Refractory (RVRP)	Right Ventricular Refractory Period is the time period following a right ventricular event, either paced or sensed, when sensed electric activity in the right ventricle does not reset the timing cycles.	ST	ms
GDT-00049	LV-Refractory (LVRP)	Left Ventricular Refractory Period (LVRP) is defined as the time period following a left ventricular event, either paced or sensed, when intrinsic LV events will not be used to reset the timing cycles.	NM	ms
GDT-00050	LV Protection Period	Left Ventricular Protection Period (LVPP): LVPP is the period after a left ventricular event, either paced or sensed, when the device will not pace the left ventricle.	NM	ms
GDT-00051	Ventricular Pacing Chamber	Pacing Chamber: This parameter determines the ventricular pacing configuration - left, -right or bi-ventricular pacing.	ST	
GDT-00052	Ventricular Pacing Chamber LV Offset	Offset between delivery of RV and LV pacing pulses. The offset is applied to the LV pacing pulse, based on the timing of the RV pacing pulse. The offset may have a negative or positive value.	NM	ms
GDT-00053	Pacing Output - RA	The combination of the Right Atrial Amplitude and the Right Atrial Pulse Width.	ST	
GDT-00054	Pacing Output - RV	The combination of the Right Ventricular Amplitude and the Right Ventricular Pulse Width.	ST	

OBX terms used in OBR-1 group (Last interrogation data)

Not every term appears in every message

GDT Code	Term Name	Description	Data Type	Unit
GDT-00055	Pacing Output - LV	The combination of the Left Ventricular Amplitude and the Left Ventricular Pulse Width.	ST	
GDT-00056	ATR Mode Switch Mode	ATR Mode Switch Mode: Non-tracking pacing mode change when patient experiences atrial tachyarrhythmia.	ST	
GDT-00057	ATR Mode Switch Rate	Atrial Tachy Response Rate is the pacing rate to which the mode switches in a new therapy setting.	ST	min ⁻¹
GDT-00074	VF Zone	VF Rate Threshold: The rate above which an R-R interval is classified in the VF zone.	NM	min ⁻¹
GDT-00075	VF Shock 1 Energy	VF Shock 1 Energy: The amount of energy delivered in the first shock of the VF zone.	NM	J
GDT-00076	VF Shock 2 Energy	VF Shock 2 Energy: The amount of energy delivered in the second shock of the VF zone.	NM	J
GDT-00077	VF Max Shock Energy	VF Maximum Shock Energy: The amount of energy delivered in each remaining shock after the second shock of the VF zone.	NM	J
GDT-00078	VF Number Of Additional Shocks	VF Number Of Additional Shocks: The number of additional max energy shocks in the VF zone programmed for delivery.	NM	
GDT-00079	<ul style="list-style-type: none"> • VT Zone • Tachy Detection Rate 	VT Rate Threshold: The rate above which an R-R interval is classified in the VT zone.	NM	min ⁻¹
GDT-00080	VT Zone ATP1 Type	The type of ventricular Antitachy Pacing bursts delivered in the VT Zone by an implanted device for the first programmed ventricular therapy set.	ST	
GDT-00081	VT Zone ATP1 Number of Bursts	The number of ventricular Antitachy Pacing bursts delivered in the VT Zone by an implanted device for the first programmed ventricular therapy set.	ST	
GDT-00082	VT Zone ATP2 Type	The type of ventricular Antitachy Pacing bursts delivered in the VT Zone by an implanted device for the second programmed ventricular therapy set.	ST	
GDT-00083	VT Zone ATP2 Number of Bursts	The number of ventricular Antitachy Pacing bursts delivered in the VT Zone by an implanted device for the second programmed ventricular therapy set.	ST	
GDT-00084	VT Shock 1 Energy	VT Shock 1 Energy: The amount of energy delivered in the first shock of the VT zone.	ST	J

OBX terms used in OBR-1 group (Last interrogation data)

Not every term appears in every message

GDT Code	Term Name	Description	Data Type	Unit
GDT-00085	VT Shock 2 Energy	VT Shock 2 Energy: The amount of energy delivered in the second shock of the VT zone.	ST	J
GDT-00086	VT Max Shock Energy	VT Maximum Shock Energy: The amount of energy delivered in each remaining shock after the second shock of the VT zone.	ST	J
GDT-00087	VT Number Of Additional Max Energy Shocks	VT Number Of Additional Shocks: The number of additional max energy shocks in the VT zone programmed for delivery.	NM	
GDT-00088	VT-1 Zone	VT-1 Rate Threshold: The rate above which an R-R interval is classified in the VT-1 zone.	NM	min ⁻¹
GDT-00089	VT-1 ATP1 Type	The type of ventricular Antitachy Pacing bursts delivered in the VT-1 Zone by an implanted device for the first ventricular therapy set.	ST	
GDT-00090	VT-1 ATP1 Number of Bursts	The number of ventricular Antitachy Pacing bursts delivered in the VT-1 Zone by an implanted device for the first ventricular therapy set.	ST	
GDT-00091	VT-1 ATP2 Type	The type of ventricular Antitachy Pacing bursts delivered in the VT-1 Zone by an implanted device for the second ventricular ATP therapy set.	ST	
GDT-00092	VT-1 ATP2 Number of Bursts	The number of ventricular Antitachy Pacing bursts delivered in the VT-1 Zone by an implanted device for the second ventricular ATP therapy set.	ST	
GDT-00093	VT-1 Shock 1 Energy	VT-1 Shock 1 Energy: The amount of energy delivered in the first shock of the VT-1 zone.	ST	J
GDT-00094	VT-1 Shock 2 Energy	VT-1 Shock 2 Energy: The amount of energy delivered in the second shock of the VT-1 zone.	ST	J
GDT-00095	VT-1 Max Shock Energy	VT-1 Maximum Shock Energy: The amount of energy delivered in each remaining shock after the second shock of the VT-1 zone.	ST	J
GDT-00096	VT-1 Number Of Additional Max Energy Shocks	VT-1 Number Of Additional Shocks: The number of shocks in the VT-1 zone programmed for delivery.	NM	
GDT-00097	Counters Since	The starting date that the counter values are calculated from.	ST	

OBX terms used in OBR-1 group (Last interrogation data)

Not every term appears in every message

GDT Code	Term Name	Description	Data Type	Unit
GDT-00108	Device Implant Date	Implant date of the device <i>NOTE: The observation value will either conform to the DT format or show "N/R"</i>	DT	
GDT-00119	RV Pace Threshold	The minimum electrical stimulation (pacemaker output pulse) required to consistently initiate right ventricular (RV) depolarization.	ST	
GDT-00190	<ul style="list-style-type: none"> Reverse Mode Switch RYTHMIQ™ 	The alternative manner in which the device provides rate and rhythm support.	ST	
GDT-00191	<ul style="list-style-type: none"> Lead Configuration (Pace/Sense) - RA 	The configuration of the RA Lead for pacing and sensing.	ST	
GDT-00192	<ul style="list-style-type: none"> Lead Configuration (Pace/Sense) - RV 	The configuration of the RV Lead for pacing and sensing.	ST	
GDT-00193	<ul style="list-style-type: none"> Lead Configuration (Pace/Sense) - LV 	The configuration of the LV Lead for pacing and sensing.	ST	
GDT-00196	ATR Minimum Duration	Atrial Tachycardia Response Minimum Duration: The shortest duration of Atrial Tachycardia Response episodes since the "Counters Since" date.	ST	
GDT-00197	ATR Maximum Duration	Atrial Tachycardia Response Maximum Duration: The longest duration of Atrial Tachycardia Response episodes since the "Counters Since" date.	ST	
GDT-00200	Magnet Rate	The expected rate when a magnet is placed over the device, an indicator of remaining battery life.	NM	min ⁻¹
GDT-00201	Minute Ventilation	This parameter specifies the MV sensor mode for the rate adaptive pacing. Values can be On, Off, Passive, or ATROnly.	ST	
GDT-00207	Accelerometer	This parameter specifies the XL sensor mode for the rate adaptive pacing. Values can be On, Off, Passive, or ATROnly.	ST	
GDT-00212	MRI Protection Mode	This counts the number of times MRI Protection was started since the last implanted device reset.	NM	
GDT-00213	RA Pace Threshold	The minimum electrical stimulation (pacemaker output pulse) required to consistently initiate right atrial (RA) depolarization.	ST	
GDT-00216	<ul style="list-style-type: none"> Ventricular Tachy EGM Storage Tachy EGM Storage 	Parameter to determine if Tachy EGM storage is on or off. Brady devices only.	ST	

OBX terms used in OBR-1 group (Last interrogation data)

Not every term appears in every message

GDT Code	Term Name	Description	Data Type	Unit
GDT-00217	VF Zone ATP	Indicates whether or not ATP therapy is enabled in the VF zone.	ST	
GDT-00218	AV Search Hysteresis AV Delay	The AV delay to be applied when the device is in an AV search.	NM	ms
GDT-00219	LV Pace Threshold	The minimum electrical stimulation (pacemaker output pulse) required to consistently initiate left ventricular (LV) depolarization.	ST	
GDT-01001	Device Report	A combination of one or more device reports from the in-clinic follow-up session in PDF format	ED	

OBX terms used in OBR–2 group (Implant data)

Not every term appears in every message

GDT Code	Term Name	Description	Data Type	Unit
GDT-00001	Result Source	The Result Source identifies the source of the data (i.e., Implant).	ST	
GDT-00002	Device Manufacturer	Device manufacturer company name.	ST	
GDT-00003	Device Type	The type of device.	ST	
GDT-00004	Device Name	The name given to a device by the manufacturer.	ST	
GDT-00005	Device Model Name	The device model name.	ST	
GDT-00006	Device Model Number	The device model number.	ST	
GDT-00007	Device Serial Number	The device serial number.	ST	
GDT-00098	RA Intrinsic Amplitude	Right Atrial Intrinsic Amplitude (P-Wave) measured during an Intrinsic Amplitude Test.	ST	mV
GDT-00099	RA Pace Impedance	Right Atrial Lead Impedance measured during a Lead Impedance Test.	ST	Ohms
GDT-00100	RA Pace Threshold	The minimum electrical stimulation (pacemaker output pulse) required to consistently initiate Right Atrial depolarization.	ST	
GDT-00101	RV Intrinsic Amplitude	Right Ventricular Intrinsic Amplitude (R-Wave) measured during an Intrinsic Amplitude Test.	ST	mV
GDT-00102	RV Pace Impedance	Right Ventricular Lead Impedance measured during a Lead Impedance Test.	ST	Ohms
GDT-00103	RV Pace Threshold	The minimum electrical stimulation (pacing output pulse) required to consistently initiate Right Ventricular depolarization.	ST	
GDT-00104	LV Intrinsic Amplitude	Left Ventricular Intrinsic Amplitude (R-Wave) measured during an Intrinsic Amplitude Test.	ST	mV
GDT-00105	LV Pace Impedance	Left Ventricular Lead Impedance measured during a Lead Impedance Test.	ST	Ohms
GDT-00106	LV Pace Threshold	The minimum electrical stimulation (pacing output pulse) required to consistently initiate Left Ventricular depolarization.	ST	
GDT-00107	Shock Impedance	Last Delivered Ventricular Shock Lead Impedance: The shocking impedance from the last ventricular shock delivered.	ST	Ohms
GDT-00108	Device Implant Date	Implant date of the device <i>NOTE: The observation value will either conform to the DT format or show "N/R."</i>	DT	

OBX terms used in OBR-4 group (Lead information data)

Not every term appears in every message

GDT Code	Term Name (See note 1))	Description	Data Type	Unit
GDT-00120	Lead 1: Implant Date	The Implant Date of the lead.	DT	
GDT-00121	Lead 1: Manufacturer	The Manufacturer of the lead.	ST	
GDT-00122	Lead 1: Model Number	The Model of the lead.	ST	
GDT-00123	Lead 1: Serial Number	The Serial number of the lead.	ST	
GDT-00124	Lead 1: Polarity	The Polarity of the lead.	ST	
GDT-00125	Lead 1: Position	The Position of the lead.	ST	
GDT-00130	Lead 2: Implant Date	The Implant Date of the lead.	DT	
GDT-00131	Lead 2: Manufacturer	The Manufacturer of the lead.	ST	
GDT-00132	Lead 2: Model Number	The Model of the lead.	ST	
GDT-00133	Lead 2: Serial Number	The Serial number of the lead.	ST	
GDT-00134	Lead 2: Polarity	The Polarity of the lead.	ST	
GDT-00135	Lead 2: Position	The Position of the lead.	ST	
GDT-00140	Lead 3: Implant Date	The Implant Date of the lead.	DT	
GDT-00141	Lead 3: Manufacturer	The Manufacturer of the lead.	ST	
GDT-00142	Lead 3: Model Number	The Model of the lead.	ST	
GDT-00143	Lead 3: Serial Number	The Serial number of the lead.	ST	
GDT-00144	Lead 3: Polarity	The Polarity of the lead.	ST	
GDT-00145	Lead 3: Position	The Position of the lead.	ST	
GDT-00150	Lead 4: Implant Date	The Implant Date of the lead.	DT	
GDT-00151	Lead 4: Manufacturer	The Manufacturer of the lead.	ST	
GDT-00152	Lead 4: Model Number	The Model of the lead.	ST	
GDT-00153	Lead 4: Serial Number	The Serial number of the lead.	ST	
GDT-00154	Lead 4: Polarity	The Polarity of the lead.	ST	
GDT-00155	Lead 4: Position	The Position of the lead.	ST	
GDT-00160	Lead 5: Implant Date	The Implant Date of the lead.	DT	
GDT-00161	Lead 5: Manufacturer	The Manufacturer of the lead.	ST	
GDT-00162	Lead 5: Model Number	The Model of the lead.	ST	
GDT-00163	Lead 5: Serial Number	The Serial number of the lead.	ST	
GDT-00164	Lead 5: Polarity	The Polarity of the lead.	ST	
GDT-00165	Lead 5: Position	The Position of the lead.	ST	

OBX terms used in OBR-4 group (Lead information data)

Not every term appears in every message

GDT Code	Term Name (See note 1))	Description	Data Type	Unit
GDT-00170	Lead 6: Implant Date	The Implant Date of the lead.	DT	
GDT-00171	Lead 6: Manufacturer	The Manufacturer of the lead.	ST	
GDT-00172	Lead 6: Model Number	The Model of the lead.	ST	
GDT-00173	Lead 6: Serial Number	The Serial number of the lead.	ST	
GDT-00174	Lead 6: Polarity	The Polarity of the lead.	ST	
GDT-00175	Lead 6: Position	The Position of the lead.	ST	

OBX terms used in OBR-4 group (Lead information data) Notes

1. Lead.x may or may not be viewable, depending on the version of the system.

Outdated version. Do not use.
 Version überholt. Nicht verwenden.
 Version obsolete. Ne pas utiliser.
 Versión obsoleta. No utilizar.
 Versione obsolete. Non utilizzare.
 Verouderde versie. Niet gebruiken.
 Föråldrad version. Använd ej.
 Παλιά έκδοση. Μην την χρησιμοποιείτε.
 Versão obsoleta. Não utilize.
 Forældet version. Må ikke anvendes.
 Zastaralá verze. Nepoužívat.
 Utdatert versjon. Skal ikke brukes.
 Zastaraná verzia. Nepoužívať.
 Elavult verzió. Ne használja!
 Wersja nieaktualna. Nie używać.

Example HL7 File



The following example HL7 file shows what a LATITUDE Link message might look like. This is only one example of the many possible outcomes. Data within the example message is hypothetical and not all terms are represented.

```
MSH|^~\&|LATITUDE Link|BOSTON SCIENTIFIC||The
Clinic|20140715152015+0000||ORU^R01|55963320140715152015|P|2.3.1|||NE|||8859/
1|en^English^ISO639
PID|1|m:N118/s:559633|m:N118/s:559633||TEST^SAMPLE||19530514|U
NTE|1|LATITUDE|\br\Device Status\br\-----\br\Jul 15, 2014
09:41 - Ventricular Tachy mode set to value other than Monitor+Therapy
PV1|1|R
OBR|1||255|BostonScientific-LastInterrogation^Last
Interrogation|||201407150941|201407150941|||DR|||201407150941|||F
OBX|1|ST|GDT-00001^Result Source^GDT-LATITUDE||In-Clinic Interrogation|||F
OBX|2|ST|GDT-00002^Device Manufacturer^GDT-LATITUDE||BOSTON SCIENTIFIC|||F
OBX|3|ST|GDT-00003^Device Type^GDT-LATITUDE||CRT-D|||F
OBX|4|ST|GDT-00004^Device Name^GDT-LATITUDE|||F
OBX|5|ST|GDT-00005^Device Model Name^GDT-LATITUDE||COGNIS 100-D|||F
OBX|6|ST|GDT-00006^Device Model Number^GDT-LATITUDE||N118|||F
OBX|7|ST|GDT-00007^Device Serial Number^GDT-LATITUDE||559633|||F
OBX|8|DT|GDT-00108^Device Implant Date^GDT-LATITUDE||20081009|||F
OBX|9|ED|GDT-01001^Device Report^GDT-LATITUDE||Application^PDF^Base64^{encoded PDF
included here}|||F||201407150941
OBX|10|NM|GDT-00008^Battery Gauge^GDT-LATITUDE||100|%|||F
OBX|11|ST|GDT-00009^Battery Status^GDT-LATITUDE||Approximate time to explant: 4.5
years|||F
OBX|12|NM|GDT-00011^Charge Time^GDT-LATITUDE||9.4|s|||F
OBX|13|DT|GDT-00012^Last Reform^GDT-LATITUDE||20140630|||F
OBX|14|ST|GDT-00097^Counters Since^GDT-LATITUDE||20140603|||F
OBX|15|NM|GDT-00020^Atrial Percent Paced^GDT-LATITUDE||0|%|||F
OBX|16|NM|GDT-00021^RV Percent Paced^GDT-LATITUDE||100|%|||F
OBX|17|NM|GDT-00022^LV Percent Paced^GDT-LATITUDE||100|%|||F
OBX|18|ST|GDT-00013^VF Episodes^GDT-LATITUDE||2|||F
OBX|19|ST|GDT-00014^VT Episodes^GDT-LATITUDE||0|||F
OBX|20|ST|GDT-00015^VT-1 Episodes^GDT-LATITUDE||2|||F
OBX|21|ST|GDT-00016^Non-Sustained Ventricular Episodes^GDT-LATITUDE||0|||F
OBX|22|NM|GDT-00017^ATR Episodes^GDT-LATITUDE||30|||F
OBX|23|NM|GDT-00074^VF Zone^GDT-LATITUDE||200|bpm|||F
OBX|24|NM|GDT-00079^VT Zone^GDT-LATITUDE||160|bpm|||F
OBX|25|NM|GDT-00088^VT-1 Zone^GDT-LATITUDE||140|bpm|||F
OBX|26|ST|GDT-00034^Tachy Mode^GDT-LATITUDE||Monitor Only|||F
OBX|27|ST|GDT-00036^Brady Mode^GDT-LATITUDE||DDD|||F
OBX|28|NM|GDT-00037^Lower Rate Limit^GDT-LATITUDE||65|ppm|||F
OBX|29|NM|GDT-00038^Maximum Tracking Rate^GDT-LATITUDE||115|ppm|||F
OBX|30|ST|GDT-00043^Paced AV Delay^GDT-LATITUDE||130 - 130|ms|||F
OBX|31|ST|GDT-00044^Sensed AV Offset^GDT-LATITUDE||80 - 80|ms|||F
OBX|32|ST|GDT-00047^A-Refractory (PVARP)^GDT-LATITUDE||280 - 280|ms|||F
OBX|33|ST|GDT-00048^RV-Refractory (RVRP)^GDT-LATITUDE||250 - 250|ms|||F
OBX|34|NM|GDT-00049^LV-Refractory (LVRP)^GDT-LATITUDE||250|ms|||F
OBX|35|ST|GDT-00051^Ventricular Pacing Chamber^GDT-LATITUDE||BiV|||F
OBX|36|NM|GDT-00052^Ventricular Pacing Chamber LV Offset^GDT-LATITUDE||0|ms|||F
OBX|37|NM|GDT-00050^LV Protection Period^GDT-LATITUDE||400|ms|||F
OBX|38|ST|GDT-00056^ATR Mode Switch Mode^GDT-LATITUDE||VDI|||F
OBX|39|ST|GDT-00057^ATR Mode Switch Rate^GDT-LATITUDE||170|bpm|||F
OBX|40|ST|GDT-00053^Pacing Output - RA^GDT-LATITUDE||2.5 V @ 0.4 ms|||F
OBX|41|ST|GDT-00054^Pacing Output - RV^GDT-LATITUDE||2.5 V @ 0.4 ms|||F
OBX|42|ST|GDT-00055^Pacing Output - LV^GDT-LATITUDE||2.5 V @ 0.4 ms|||F
OBX|43|ST|GDT-00040^Sensitivity RA^GDT-LATITUDE||AGC 0.25|mV|||F
OBX|44|ST|GDT-00041^Sensitivity RV^GDT-LATITUDE||AGC 0.6|mV|||F
OBX|45|ST|GDT-00042^Sensitivity LV^GDT-LATITUDE||AGC 1.0|mV|||F
OBX|46|ST|GDT-00191^Lead Configuration (Pace/Sense) - RA^GDT-LATITUDE||Bipolar|||F
OBX|47|ST|GDT-00192^Lead Configuration (Pace/Sense) - RV^GDT-LATITUDE||Bipolar|||F
OBX|48|ST|GDT-00193^Lead Configuration (Pace/Sense) - LV^GDT-LATITUDE||LVtip>>RV|||F
```


OBX|49|ST|GDT-00207^Accelerometer^GDT-LATITUDE||Off|||||F
 OBX|50|ST|GDT-00023^Right Atrial Lead Status^GDT-LATITUDE||OK|||||F
 OBX|51|ST|GDT-00024^RA Intrinsic Amplitude^GDT-LATITUDE||3.0|mV|||||F||20140715
 OBX|52|ST|GDT-00025^RA Pace Impedance^GDT-LATITUDE||544|Ohms|||||F||20140715
 OBX|53|ST|GDT-00213^RA Pace Threshold^GDT-LATITUDE||1.4 V @ 0.4 ms|||||F||20140715
 OBX|54|ST|GDT-00026^Right Ventricular Lead Status^GDT-LATITUDE||OK|||||F
 OBX|55|ST|GDT-00027^RV Intrinsic Amplitude^GDT-LATITUDE||N/R|mV|||||F||20140715
 OBX|56|ST|GDT-00028^RV Pace Impedance^GDT-LATITUDE||497|Ohms|||||F||20140715
 OBX|57|ST|GDT-00119^RV Pace Threshold^GDT-LATITUDE||2.2 V @ 0.4 ms|||||F||20140715
 OBX|58|ST|GDT-00029^Left Ventricular Lead Status^GDT-LATITUDE||OK|||||F
 OBX|59|ST|GDT-00030^LV Intrinsic Amplitude^GDT-LATITUDE||N/R|mV|||||F||20140715
 OBX|60|ST|GDT-00031^LV Pace Impedance^GDT-LATITUDE||605|Ohms|||||F||20140715
 OBX|61|ST|GDT-00219^LV Pace Threshold^GDT-LATITUDE||2.0 V @ 0.4 ms|||||F||20140715
 OBX|62|ST|GDT-00032^Shock Vector Status^GDT-LATITUDE||OK|||||F
 OBX|63|ST|GDT-00033^Shock Impedance^GDT-LATITUDE||55|Ohms|||||F||20140715
 OBR|2||255|BostonScientific-
 Implant^Implant||20081009|20081009|||||||DR|||20081009|||F
 OBX|1|ST|GDT-00001^Result Source^GDT-LATITUDE||Implant|||||F
 OBX|2|ST|GDT-00002^Device Manufacturer^GDT-LATITUDE||BOSTON SCIENTIFIC|||||F
 OBX|3|ST|GDT-00003^Device Type^GDT-LATITUDE||CRT-D|||||F
 OBX|4|ST|GDT-00004^Device Name^GDT-LATITUDE|||||||F
 OBX|5|ST|GDT-00005^Device Model Name^GDT-LATITUDE||COGNIS 100-D|||||F
 OBX|6|ST|GDT-00006^Device Model Number^GDT-LATITUDE||N118|||||F
 OBX|7|ST|GDT-00007^Device Serial Number^GDT-LATITUDE||559633|||||F
 OBX|8|DT|GDT-00108^Device Implant Date^GDT-LATITUDE||20081009|||||F
 OBX|9|ST|GDT-00098^RA Intrinsic Amplitude^GDT-LATITUDE||2.0|mV|||||F
 OBX|10|ST|GDT-00099^RA Pace Impedance^GDT-LATITUDE||650|Ohms|||||F
 OBX|11|ST|GDT-00100^RA Pace Threshold^GDT-LATITUDE||2.0 V @ 0.4 ms|||||F
 OBX|12|ST|GDT-00101^RV Intrinsic Amplitude^GDT-LATITUDE||3.0|mV|||||F
 OBX|13|ST|GDT-00102^RV Pace Impedance^GDT-LATITUDE||750|Ohms|||||F
 OBX|14|ST|GDT-00103^RV Pace Threshold^GDT-LATITUDE||2.4 V @ 0.4 ms|||||F
 OBX|15|ST|GDT-00104^LV Intrinsic Amplitude^GDT-LATITUDE||3.0|mV|||||F
 OBX|16|ST|GDT-00105^LV Pace Impedance^GDT-LATITUDE||700|Ohms|||||F
 OBX|17|ST|GDT-00106^LV Pace Threshold^GDT-LATITUDE||1.8 V @ 0.4 ms|||||F
 OBX|18|ST|GDT-00107^Shock Impedance^GDT-LATITUDE||50|Ohms|||||F
 OBR|4||255|BostonScientific-Leads Lead
 Information||201407150941|201407150941|||||||DR|||201407150941|||F
 ZU1|
 ZU2|Device Summary Report Version 5

Symbols Used on Labeling

The following symbols are used in this literature:

SYMBOL	DEFINITION
	Manufacturer
	Authorized Representative in the European Community

Outdated version. Do not use.
 Version überholt. Nicht verwenden.
 Version obsolète. Ne pas utiliser.
 Versión obsoleta. No utilizar.
 Versione obsolete. Non utilizzare.
 Verouderde versie. Niet gebruiken.
 Föråldrad version. Använd ej.
 Παλιά έκδοση. Μην την χρησιμοποιείτε.
 Versão obsoleta. Não utilize.
 Forældet version. Må ikke anvendes.
 Zastaralá verze. Nepoužívat.
 Utdatert versjon. Skal ikke brukes.
 Zastaraná verzia. Nepoužívať.
 Elavult verzió. Ne használja!
 Wersja nieaktualna. Nie używać.

Outdated version. Do not use.
Version überholt. Nicht verwenden.
Version obsolète. Ne pas utiliser.
Versión obsoleta. No utilizar.
Versione obsoleta. Non utilizzare.
Verouderde versie. Niet gebruiken.
Föråldrad version. Använd ej.
Παλιά έκδοση. Μην την χρησιμοποιείτε.
Versão obsoleta. Não utilize.
Forældet version. Må ikke anvendes.
Zastaralá verze. Nepoužívat.
Utdatert versjon. Skal ikke brukes.
Zastaraná verzia. Nepoužívať.
Elavult verzió. Ne használja!
Wersja nieaktualna. Nie używać.

Boston Scientific



Boston Scientific
4100 Hamline Avenue North
St. Paul, MN 55112-5798 USA



Guidant Europe NV/SA; Boston Scientific
Green Square, Lambroekstraat 5D
1831 Diegem, Belgium

1.800.CARDIAC (227.3422)
+1.651.582.4000

www.bostonscientific.com

© 2014 Boston Scientific Corporation or its affiliates.
All rights reserved.

359382-001 EN UK 2014-08

